



REQUIREMENTS:

- 1:100% short,open and miss wire test.
- 2:Insulation resistance:DC300V 10MΩ(Min)
Conduction resistance 5Ω(Max)

⑥	OUTER MOLDED	BLACK 45P PVC	0.048	KG
⑤	INTER MOLDED	LDPE	0.021	KG
④	SCREW	#4-40UNC 2.3*45.5MM,NICKEL PLATED,WITH BLACK PVC	4	PCS
③	FERRITE CORE	F5B:RH12*20*7.3	2	PCS
②	CONNECTOR	DVI 18+1/MALE,BLACK INSULATOR,GOLD PLATED SHELL,GOLD PLATED PIN	2	PCS
①	CABLE	(1P*30#+FME+D+AL+MYLAR)*4C+1P*30#+3C*30#+ADB JACKET:BLACK PVC OD:6.0±0.2MM	3000	MM

Ltemref	Quantity	Title/Name,designation,material,dimension etc		Article No./Reference
Designed by ACHY		Checked by HELEN	Approved by - date OCT 23,2014	File name DVI18+1M/M 3M
ANGLE: UNIT:MM				Date OCT 23,2014
				DVI 24+1 M-M 30AWG 3M
				32 2806
				Edition 1
				Scale FREE
				Sheet 1/1

