



RevNo	Revision note	Date	Signature	Checked
-------	---------------	------	-----------	---------



SHELL _____ SHELL

④	OUTER MOLDED	BLACK 45P PVC	0.021	KG
③	CONNECTOR	USB B TYPE MALE,WHITE INSULATOR,NICKEL PLATED SHELL,GOLD PLATED PIN	1	PCS
②	CONNECTOR	USB A TYPE MALE,WHITE INSULATOR,NICKEL PLATED SHELL,GOLD PLATED PIN	1	PCS
①	CABLE	USB2.0 1P*28#+2C*28#+AB OD:3.9±0.1 JACKET:BLACK PVC MARKING:AWM STYLE 2725 80t 30V VW-1 USB2.0 High Speed Cable-ROHS	5	M
NO.	MATERIAL	DESCRIPTIONG	QTY.	UNIT

1:100% short,open and miss wire test.
 2:Insulation resistance:DC300V 10MΩ(Min)
 Conduction resistance 5Ω(Max)

REQUIREMENTS:

Ltemref	Quantity	Title/Name,designation,material,dimension etc	Article No./Reference
Designed by ACHY	Checked by HELEN	Approved by - date MARCH 6,2012	File name USB AM TO BM L-5M
Date MARCH 6,2012		Scale FREE	
Edition 1		Sheet 1/1	

