



P/N:

P/N	L(MM)	T(MM)
V1AD-SVGA	1000	±50
V2AD-SVGA	2000	±70
V3AD-SVGA	3000	±70
V5AD-SVGA	5000	±70
V10AD-SVGA	10000	±150
V15AD-SVGA	15000	±200

REQUIREMENTS:

1:100% short,open and miss wire test.

NO.	MATERIAL	DESCRIPTIONG	QTY.	UNIT
⑧	OUTER MOLDED	BLACK 45P PVC	0.048	KG
⑦	INTER MOLDED	LDPE	0.021	KG
⑥	SCREW	#4-40UNC 2.3*45.5MM,WITH BLACK PVC	4	PCS
⑤	FERRITE CORE	F5B:RH14.2*28.5*9.5	2	PCS
④	CONNECTOR	STEREO DC3.5 MALE,BLACK INSULATOR,NICKEL PLATED SHELL	2	PCS
③	CONNECTOR	HDB 15PIN/MALE,BLACK INSULATOR,NICKEL PLATED PIN	2	PCS
②	CABLE	28#*2C+SPIRAL JACKET:BLACK PVC, OD:3.0±0.15,NO MARKING.	1150	MM
①	CABLE	(1C*28#+FPE+D+FAM)*3C+11C*28#+ADB JACKET:BLACK PVC OD:9.0±0.2 MARKING:AWM STYLE 2919 80°C 30V LOW VOLTAGE COMPUTER CABLE ROHS COMPLIANT	L	MM

PIN OUT

P1	P2	P1	P2
1	1	4	4
2	2	5	5
3	3	9	9
6	6	10	10
7	7	11	11
8	8	12	12
shell	shell	13	13
P3.3	P3.3	14	14
P3.2	P3.2	15	15
P3.1	P3.1		

Itemref	Quantity	Title/Name,designation,material,dimension etc	Article No./Reference
Designed by	Checked by	Approved by - date	File name
ACHY	HELEN	JUNE 17.2013	VxxAD-SVGA
ANGLE:	VGA(3+9)+AUDIO M TO M		
UNIT:MM	VxxAD-SVGA		
	1	Edition	Sheet
		1	1/1